



**Interchangeable  
with PCS®  
“TL” Series**

- All sharp edges are chamfered
- Self-locking screws are included
- Will not seize under thermal expansion
- Provides positive, accurate alignment
- Special sizes made to your requirements
- Parts are machined symmetrically to the centerline
- Male Top Lock
  - Manufactured from Graphite O-6 Steel
  - Hardened to 60-62 Rc
  - Black Oxide Finish
- Female Top Lock
  - Manufactured from 8620 Steel
  - Hardened to 54-56 Rc
  - Armor-Dense Chrome Plating 70-72 Rc providing excellent wear resistance
  - Notched for easy removal

## External

W	T	D	Overall Height	A	E1	E2	F	R	B	SHCS Male (2)	SHCS Female (2)	Catalog Number
1.0000	.500	.275	.875	.3750	.250	.688	.500	.187	.375	6-32 x 1/2	6-32 x 5/8	TL1000
1.2500	.625	.375	1.125	.4380	.312	.875	.625	.250	.500	6-32 x 1/2	6-32 x 5/8	TL1250
1.5000	.875	.500	1.625	.5000	.437	1.000	.875	.250	.750	8-32 x 3/4	8-32 x 3/4	TL1500
2.0000	1.000	.625	1.875	.7500	.500	1.375	1.125	.375	.750	10-32 x 3/4	10-32 x 1	TL2000
3.0000	1.125	.750	2.250	1.1250	.562	2.250	1.500	.500	.750	1/4-20 x 3/4	1/4-20 x 1-1/2	TL3000

## Internal

W	T	D	Overall Height	A	E1	E2	F	R	B	SHCS Male (2)	SHCS Female (2)	Catalog Number
1.0000	.500	.275	.875	.3750	.250	.688	.500	.187	.375	6-32 x 1/2	6-32 x 5/8	TL1000R
1.2500	.625	.375	1.125	.4380	.312	.875	.625	.250	.500	6-32 x 1/2	6-32 x 5/8	TL1250R
1.5000	.875	.500	1.625	.5000	.437	1.000	.875	.250	.750	8-32 x 3/4	8-32 x 3/4	TL1500R
2.0000	1.000	.625	1.875	.7500	.500	1.375	1.125	.375	.750	10-32 x 3/4	10-32 x 1	TL2000R
3.0000	1.125	.750	2.250	1.1250	.562	2.250	1.500	.500	.750	1/4-20 x 3/4	1/4-20 x 1-1/2	TL3000R

Progressive® and PCS® are the property of their respective companies